

DPW-6 Results Using FUN3D

With Focus on k-kL-MEAH2015 Turbulence Model

Khaled S. Abdol-hamid

Chris Rumsey

Jan Carlson

Mike Park

NASA Langley Research Center, Hampton, VA

June 2016

Overview

- Brief description of FUN3D and the k-kL-MEAH2015 turbulence model
- NACA 0012 Verification Case
- WB and WBNP configurations
 - Grid study ($C_L=0.5$)
- WB Case
 - C_L , C_D and C_m variations with angle of attack
- Results related to:
 - Effect of using limiter
 - Turbulence Models: k-kL-MEAH2015, SA, and SST


FUN3D

- Node-based finite-volume solver for mixed element grids
- Blended upwind (Roe) and UMUSCL with $\kappa=0.5$
- Tested both with no limiter and with hminmod limiter (stencil-based min-mod limiter from Barth augmented with a heuristic pressure limiter)
- Full Navier-Stokes terms
- Most turbulence models solved loosely-coupled to mean flow equations
- Adjoint-based adaptation and design-optimization capability (not used for this study)
- <http://fun3d.larc.nasa.gov>

k-kL-MEAH2015 Turbulence Model

$$\frac{\partial \rho k}{\partial t} + \frac{\partial \rho U_j k}{\partial x_j} = \left[P_k + \frac{\partial}{\partial x_j} \left(\mu_l + \sigma_k \mu_t \frac{\partial k}{\partial x_j} \right) - 2\mu_l \frac{k}{d^2} \right] - C_k \rho \frac{k^{2.5}}{(kL)}$$

$$\frac{\partial \rho(kL)}{\partial t} + \frac{\partial \rho U_j (kL)}{\partial x_j} = \left[C_{(kL)1} \frac{(kL)}{k} P_k + \frac{\partial}{\partial x_j} \left(\mu_l + \sigma_{(kL)} \mu_t \frac{\partial (kL)}{\partial x_j} \right) - 6\mu_l \frac{(kL)}{d^2} f_{kL} \right] - C_{(kL)2} \rho k^{1.5}$$

$$\mu_t = C_\mu^{1/4} \frac{\rho(kL)}{k^{1/2}}$$


This term based on the SAS formulation of Menter and Egorov; however, in Hamid's formulation the model functions as steady RANS as grid is refined

wall Boundary Conditions:

$$k_w = 0.0$$

$$(kL)_w = 0.0$$


See NASA/TM-2015-218968 Nov 2015 or AIAA-2016-3941 (w/o correction terms)

Case 1

NACA 0012 Grid Study

NACA 0012

$M=0.15$, $Re=6.0 \times 10^6$, $\alpha=10^\circ$




Level	Nodes
6	14,625
5	57,921
4	230,529
3	919,809
2	3,674,625
1	14,689,281

NACA 0012



$M=0.15$, $Re=6.0 \times 10^6$, $\alpha=10$ deg

Comparison of k-kL-MEAH2015 results with SA results from FUN3D



NACA 0012, k-kL-MEAH2015

$M=0.15$, $Re=6.0 \times 10^6$, $\alpha=10$ deg





Three finest grid results are practically indistinguishable

Level 1 is finest grid

NACA 0012, k-kL-MEAH2015

$M=0.15$, $Re=6.0 \times 10^6$, $\alpha=10$ deg




... except when zoomed in

Level 1 is finest grid

NACA 0012, k-kL-MEAH2015

$M=0.15$, $Re=6.0 \times 10^6$, $\alpha=10$ deg




Effect of grid is minimal near body, but significant in the wake at $x/c=10$
(similar to SA results on TMR website)

Level 1 is finest grid

WB/WBNP CRM Configurations

Case 2, $M=0.85$, $Re=5.0 \times 10^6$

$C_L=0.5000 \pm 0.0001$ Grid Study 400-3000 CPUs




Mean Aerodynamic Chord (c_{ref})	275.80 inch
Wing Reference Area/2	297,360 inch ²
Wing Span/2	1,159.75 inch
X Moment Center	1,325.9 inch
Z Moment Center	177.95 inch
Aspect Ratio(AR)	9.0

Level	WB Nodes	WBNP Nodes
Tiny	20,472,098	27,774,771
Course	29,916,005	40,816,155
Medium	44,249,828	60,686,493
Fine	66,228,067	91,140,011
X-Fine	100,781,934	138,477,189
U-Fine	151,316,926	208,732,968


Used: Unstr. NASA GeoLab Rev 0, mixed elements

WB CRM Configuration


$C_L=0.5000\pm0.0001$ Grid Study 400-2000 CPUs



Coarse



Fine






Ufine

Fixed C_L runs start from $\alpha=2.75$ deg result at different grid level, then turn on automated C_L driver

WB CRM Configuration

$C_L = 0.5000 \pm 0.0001$ Grid Study 400-2000 CPUs

Limiter effect on results




The variations of results with grid refinement are smaller when using hminmod limiter
Differences between no-limiter vs. limiter generally decrease as grid refined

WBNP CRM Configuration

$C_L = 0.5000 \pm 0.0001$ Grid Study 600-3000 CPUs

Limiter effect on results




The variations of results with grid refinement are smaller when using hminmod limiter
Differences between no-limiter vs. limiter generally decrease as grid refined

Nacelle/Pylon Effect

$C_L=0.5000\pm0.0001$ Grid Study 600-3000 CPUs

Using no limiter




- 8.4 to 8.6 % change in drag
- -7.3 to -8.3 % change in moment
- 5.6 to 6.5% change in α

Nacelle/Pylon Effect

$C_L=0.5000\pm0.0001$ Grid Study 600-3000 CPUs

Using hminmod limiter



- 8.85 to 9.04 % change in drag
- -6.95 to -7.6% change in moment
- 6.14 to 6.54 % change in α


Case 3

Wing Body CRM Configuration
Medium Grid $M=0.85$, $Re=5.0 \times 10^6$
 $\alpha = 2.50, 2.75, 3.00, 3.25, 3.50, 3.75$
and 4.00 deg

Wing Body CRM Configuration

Case 3, 800 CPUs, $M=0.85$, $Re=5.0 \times 10^6$

$\alpha=2.50, 2.75, 3.00, 3.25, 3.50, 3.75$ and 4.00 deg



Mean Aerodynamic Chord (c_{ref})	275.80 inch
Wing Reference Area/2	297,360 inch ²
Wing Span/2	1,159.75 inch
X Moment Center	1,325.9 inch
Z Moment Center	177.95 inch
Aspect Ratio(AR)	9.0

α , deg	Nodes
2.50	44,254,225
2.75	44,249,828
3.00	44,174,034
3.25	44,180,700
3.50	44,2426,17
3.75	44,217,067
4.00	44,238,097


Used: Unstr. NASA GeoLab Rev 0, mixed elements

Wing Body CRM Configuration

$$M=0.85, Re=5.0 \times 10^6$$

$\alpha=2.50, 2.75, 3.00, 3.25, 3.50, 3.75$ and 4.00 deg

Linear Turbulence Models Using No Limiter




SA shows early large separation ($\alpha > 3.25$ deg)
k-kL-MEAH2015 shows trend similar to WT data
SST shows early large separation ($\alpha > 3.50$ deg)

Wing Body CRM Configuration

$$M=0.85, Re=5.0 \times 10^6$$

$\alpha=2.50, 2.75, 3.00, 3.25, 3.50, 3.75$ and 4.00 deg


Effect of Limiter on k-kL-MEAH2015 Results



On this grid level, there are noticeable changes in the polars when running no-limiter vs. hminmod limiter

Convergence of SA and k-kL-MEAH2015


$\alpha=2.50$ deg



Stopping criterion: change in C_L and C_D less than 0.1% in last 1000 iterations and less than 0.05% in last 500 iterations; in all cases, residuals for all computed variables dropped by at least 4 orders

$C_{f,x}$ for SA and k-kL-MEAH2015 Results


$\alpha=2.50$ deg



SA shows trend toward separated flow at the base of the wing;
k-kL-MEAH2015 does not


$C_{f,x}$ for SA and k-kL-MEAH2015 Results

$\alpha = 2.75$ deg




$C_{f,x}$ for SA and k-kL-MEAH2015 Results

$\alpha=3.00$ deg



$C_{f,x}$ for SA and k-kL-MEAH2015 Results


$\alpha=3.25$ deg



SA shows start of wing-root side-of-body (SOB) separation

$C_{f,x}$ for SA and k-kL-MEAH2015 Results


$\alpha=3.50$ deg



SA's wing-root SOB separation grows dramatically


$C_{f,x}$ for SA and k-kL-MEAH2015 Results

$\alpha=3.75$ deg





$C_{f,x}$ for SA and k-kL-MEAH2015 Results

$\alpha=4.00$ deg




Convergence of SA and k-kL-MEAH2015

$\alpha=4.00$ deg



Effect of QCR on k-kL-MEAH2015

$\alpha=4.00$ deg



Linear and nonlinear k-kL-MEAH2015 predicted very similar results on the wing surface

Summary

- k-kL-MEAH2015 RANS model in FUN3D was run for DPW-6 cases
 - Model has simple zero wall BCs for both variables
 - This model was originally intended to improve separated (unsteady) results, but has turned out to be a good model for steady RANS
 - All cases in this study were fully steady
- For 0012 verification case, k-kL-MEAH2015 yielded C_L slightly lower and C_D slightly higher than SA model
- For CRM cases
 - k-kL-MEAH2015 was run both with and without a limiter: caused some differences (which generally decreased on finer grids)
 - Unlike SA and SST, the k-kL-MEAH2015 model did NOT produce large SOB separation even up to $\alpha=4.00$ deg (so did not stall early)
 - Reason for this success is not known
 - Use of QCR (which can help reduce SOB separation for linear models) had little influence on k-kL-MEAH2015 at alphas tested